

Prüfbericht 21-00168-CX-GBM-01
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001852

ANLAGE: 9.1
 Hersteller: MW Aftermarket Srl

Radtyp: 16655120-132
 Stand: 06.05.2022



Auto Service

Seite: 1 von 2

Manufacturer : MAN, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 60
 Hole circle (mm)/number of holes : 120/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2053	R1-2053	Without	65		1240	2171	09/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : MAN

Mounting parts : spherical collar bolt M14x1,5, diameter 28 mm

Tightening torque for fixing parts : 150 Nm

commercial type: **TGE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SYN1E	e1*2007/46*1626*..	75	205/75R16C		1); 2); 33)
SZN1E	e1*2007/46*1632*..	103 -130	235/65R16C		
			205/75R16C		
			235/65R16C		
SYN2E	e1*2007/46*1627*..	75 - 130	235/65R16C 121		1); 2); 33)
SZN2E	e1*2007/46*1633*..				

Manufacturer : MAN, VOLKSWAGEN

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M14x1,5, diameter 28 mm

Tightening torque for fixing parts : 150 Nm

commercial type: **CRAFTER MJ 2017-**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SYN1E	e1*2007/46*1613*..	75	205/75R16C		1); 2); 33)
		103 -130	235/65R16C		
			205/75R16C		
			235/65R16C		
SYN2E	e1*2007/46*1614*..	75 - 130	235/65R16C 121		1); 2); 33)
SZN2E	e1*2007/46*1620*..				
SZN1E	e1*2007/46*1619*..	75 - 130	205/75R16C		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.

Prüfbericht 21-00168-CX-GBM-01
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001852

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655120-132

Stand: 06.05.2022



Auto Service

Seite: 2 von 2

- tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.