

Prüfbericht 22-00097-CX-GBM-01
zur Erteilung der ECE (E1) 124R- 001058

ANLAGE: 9.5

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 03.03.2022



Auto Service

Seite: 1 von 1

Manufacturer : KIA**Wheel dates:**

Wheel size according to standard : 5 J X 14 H2

Off set(mm) : 49

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole	Centering material	Permissible wheel Load	Permissible rolling Circumference	Valid from
	Wheel identification	Centering identification	(mm)		(kg)	(mm)	Production date
R1-1819	R1-1819	Without	54		370	1690	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : KIA

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **Picanto or Morning**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
TA	e4*2007/46*0256*..	49 - 63	165/60R14		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.