

Prüfbericht 22-00097-CX-GBM-02
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 1 von 1

Manufacturer : HYUNDAI MOTOR (IND), KIA**Wheel dates:**

Wheel size according to standard : 5 J X 14 H2

Off set(mm) : 46

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1571	R1-1571	Without	54		420	1726	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : HYUNDAI MOTOR (IND)

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **HYUNDAI I10**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PA	e4*2001/116*0131*..	49 - 63	175/60R14		1); 2); 33)
PAG	e11*2001/116*0357*..	47 - 57	165/60R14 75		1); 2); 33)

Manufacturer : HYUNDAI MOTOR (IND), KIA

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : KIA

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **PICANTO, SA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BA	e4*2001/116*0085*..	44 - 48	165/60R14		1); 2); 33)
		55	175/60R14		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.