

Prüfbericht 21-00027-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.14
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 21.11.2022



Auto Service

Seite: 1 von 2

Manufacturer : AUTOMOBILES DACIA S.A., RENAULT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 40
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1873	R1-1873	Without	60		485	1894	35/19

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : AUTOMOBILES DACIA S.A.

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2001/116*0314*..	53 - 74	185/65R15		744; 1); 2); 33)
SD	e2*2001/116*0314*..	54 - 66	185/65R15		744; 1); 2); 33)
SD	e2*2001/116*0314*..	54 - 74	185/65R15		744; 1); 2); 33)
SD	e2*2001/116*0314*..	53 - 66	185/65R15 88		*) ; Sandero (Hatchback) from Mj 2013; 744; 1); 2); 33)
SD	e2*2001/116*0314*..	55 - 96	185/65R15		744; 75l; 1); 2); 33)
SD	e2*2001/116*0314*..	59 - 96	185/65R15		744; 75l; 1); 2); 33)
SD	e2*2001/116*0314*..	55 - 70	185/65R15 88		744; 1); 2); 33)
SD	e2*2001/116*0314*..	53 - 74	185/65R15		744; 1); 2); 33)
SD	e2*2007/46*0030*..	55 - 66	185/65R15		*) ; Sandero (Hatchback) from Mj 2013; Front wheel drive; 1); 2); 33)
SD	e2*2007/46*0030*..	55 - 85	185/65R15		*) ; only Dokker; Station wagon; Box wagon; Front wheel drive; 744; 75l; 1); 2); 33)
SD	e2*2007/46*0030*..	54 - 66	185/65R15		744; 1); 2); 33)
SD	e2*2007/46*0030*..	55 - 66	185/65R15 92		744; 75l; 1); 2); 33)

Prüfbericht 21-00027-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.14
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 21.11.2022



Auto Service

Seite: 2 von 2

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2007/46*0030*..	55 - 66	185/65R15 88		*) ; Logan (notchback) from MY 2013; 75l; 1); 2); 33)

Manufacturer : AUTOMOBILES DACIA S.A., RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts :

commercial type: **LOGAN,SANDERO, DUSTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SR	e2*2001/116*0323*..	54 - 70	185/65R15		744; 77E; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 75l) The permitted axle load of the vehicle shall not exceed the double as on page 1 of this attachment mentioned wheel load under consideration of the mentioned rolling circumference, if necessary the increased axle load in trailer operation has to be adapted or to be cancelled
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.