

**Prüfbericht 21-00027-CX-GBM-05**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.17**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
 Stand: 21.11.2022



Auto Service

Seite: 1 von 1

**Manufacturer : KIA**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2                      Off set(mm) : 46  
 Hole circle (mm)/number of holes : 100/4                      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2002	R1-2002	Without	54		475	1894	33/17

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : KIA**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 127 Nm

commercial type: **RIO, STONIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
YB	e11*2007/46*3777*..	57 - 88	185/65R15		*) ; RIO; STONIC; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.