

**Prüfbericht 21-00027-CX-GBM-05**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.8**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
 Stand: 21.11.2022



Auto Service

Seite: 1 von 2

**Manufacturer : AUTOMOBILES DACIA S.A., NISSAN, RENAULT**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2      Off set(mm) : 50  
 Hole circle (mm)/number of holes : 100/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1684	R1-1684	Without	60		585	1895	47/14
R1-1685	R1-1685	Without	60		585	1895	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : AUTOMOBILES DACIA S.A.**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : FSD/USD; SD

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : SD

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FSD/USD	N386	50 - 64	185/65R15 92		1); 2); 33)

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2001/116*0314*..	55 - 77	185/65R15 88		*) ; Station wagon; Limousine; 1); 2); 33)
SD	e2*2001/116*0314*..	50 - 77	185/65R15 88		*) ; Limousine; DF0; 1); 2); 33)
SD	e2*2001/116*0314*..	50 - 65	185/65R15 88		*) ; Sandero Stepway; to MJ 2012; von NT*29-44; 1); 2); 33)
SD	e2*2007/46*0030*..	50 - 77	185/65R15 88		*) ; Logan (notchback) to MY 2012; Sandero to MY 2012; 1); 2); 33)
SD	e2*2007/46*0030*..	84	185/65R15-88T		*) ; Dokker; 1); 2); 33)
SD	e2*2007/46*0030*..	50 - 65	185/65R15 92		*) ; Logan Express/Pickup; 1); 2); 33)

**Prüfbericht 21-00027-CX-GBM-05**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827**

**ANLAGE: 9.8**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23  
 Stand: 21.11.2022



Auto Service

Seite: 2 von 2

**Manufacturer** : **AUTOMOBILES DACIA S.A., NISSAN, RENAULT**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : **NISSAN**

Mounting parts :

commercial type: **NISSAN MICRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
K14	e9*2007/46*6454*..	52 -66	185/65R15		1); 2); 33)

**Manufacturer** : **AUTOMOBILES DACIA S.A., NISSAN, RENAULT**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : **RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN,SANDERO, DUSTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SR	e2*2007/46*0013*..	50 -65	185/65R15 92		1); 2); 33)
		50 -77	185/65R15 88		

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

### Restrictions

DF0) This wheel type is not permitted on the vehicle DACIA DUSTER.

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.