

Prüfbericht 21-00027-CX-GBM-07
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.8
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 22.05.2023



Auto Service

Seite: 1 von 2

Manufacturer : AUTOMOBILES DACIA S.A., NISSAN, RENAULT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 50
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1684	R1-1684	Without	60		585	1895	47/14
R1-1685	R1-1685	Without	60		585	1895	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : AUTOMOBILES DACIA S.A.

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : FSD/USD; SD

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : SD

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FSD/USD	N386	50 - 64	185/65R15 92		1); 2); 33)

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2001/116*0314*..	55 - 77	185/65R15 88		*) ; Station wagon; Limousine; 1); 2); 33)
SD	e2*2001/116*0314*..	50 - 65	185/65R15 88		*) ; Sandero Stepway; to MJ 2012; von NT*29-44; 1); 2); 33)
SD	e2*2001/116*0314*..	50 - 77	185/65R15 88		*) ; Limousine; DF0; 1); 2); 33)
SD	e2*2007/46*0030*..	50 - 77	185/65R15 88		*) ; Logan (notchback) to MY 2012; Sandero to MY 2012; 1); 2); 33)
SD	e2*2007/46*0030*..	84	185/65R15-88T		*) ; Dokker; 1); 2); 33)
SD	e2*2007/46*0030*..	50 - 65	185/65R15 92		*) ; Logan Express/Pickup; 1); 2); 33)

Prüfbericht 21-00027-CX-GBM-07
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.8
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 22.05.2023



Auto Service

Seite: 2 von 2

Manufacturer : AUTOMOBILES DACIA S.A., NISSAN, RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : NISSAN

Mounting parts :

commercial type: **NISSAN MICRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
K14	e9*2007/46*6454*..	52 -66	185/65R15		1); 2); 33)

Manufacturer : AUTOMOBILES DACIA S.A., NISSAN, RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN,SANDERO, DUSTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SR	e2*2007/46*0013*..	50 -65	185/65R15 92		1); 2); 33)
		50 -77	185/65R15 88		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

DF0) This wheel type is not permitted on the vehicle DACIA DUSTER.

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.