

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.1
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 17.05.2022



Auto Service

Seite: 1 von 3

Manufacturer : CITROEN, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 18
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1334	R1-1334	Without	65		615	1937	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C	e2*98/14*0153*..	65 - 85	185/65R15 88		1); 2); 33)
C****	e2*98/14*0153*..	65 - 100	185/65R15-88H		
		66 - 80	185/65HR15 M+S		

commercial type: **CITROEN XSARA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
N*DHY*	e2*93/81*0115*..	66	195/55R15		1); 2); 33)
N*DHY*	e2*98/14*0115*..	66	195/55R15		1); 2); 33)
N*KFW*	e2*98/14*0232*..	55	195/55R15 85H		1); 2); 33)
N*LFY	e2*93/81*0108*..	81	195/55R15		1); 2); 33)
N*LFY	e2*98/14*0108*..	81	195/55R15		1); 2); 33)
N*NFU*	e2*98/14*0233*..	80	195/55R15 85H 195/55R15-84V		1); 2); 33)
N*RFN*	e2*98/14*0234*..	100	195/55R15 85H 195/55R15-84V		1); 2); 33)
N*RFS	e2*93/81*0110*..	120	195/55R15		1); 2); 33)
N*RFS	e2*98/14*0110*..	120	195/55R15-84V		1); 2); 33)
N*RFV	e2*93/81*0109*..	97 - 98	195/55R15		*) Limousine; 1); 2); 33)
N*RFV	e2*98/14*0109*..	97 - 98	195/55R15		1); 2); 33)
N*RHY	e2*93/81*0189*..	66	195/55R15 85H 195/55R15-84V		1); 2); 33)
N*RHY	e2*98/14*0189*..	66	195/55R15 85H 195/55R15-84		1); 2); 33)
N*RHZ*	e2*98/14*0236*..	80	195/55R15 85H 195/55R15-84V		1); 2); 33)

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 17.05.2022



Auto Service

Seite: 2 von 3

commercial type: **CITROEN XSARA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
N*WJY*	e2*98/14*0128*..	51	195/55R15 85H		1); 2); 33)
N*8HZ*	e2*2001/116*0268*..	50	195/55R15 85H		1); 2); 33)

Manufacturer : CITROEN, PEUGEOT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT 306**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7*LFY*	e2*98/14*0148*..	81	195/55R15		1); 2); 33)
7*NFT*	e2*98/14*0241*..	72	195/55R15		1); 2); 33)
7*RHY*	e2*98/14*0081*..	66	195/55R15		1); 2); 33)

commercial type: **PEUGEOT 406**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8*BFZ	e2*93/81*0024*..	65	195/65R15		1); 2); 33)
8*BFZ	e2*98/14*0024*..	65	195/65R15		1); 2); 33)
8*DHW	e2*93/81*0023*..	55	195/65R15		1); 2); 33)
8*DHX	e2*93/81*0027*..	66	195/65R15		1); 2); 33)
8*D8B	e2*93/81*0028*..	68	195/65R15		1); 2); 33)
8*LFX	e2*93/81*0155*..	66	195/65R15		1); 2); 33)
8*LFX	e2*98/14*0155*..	66	195/65R15		1); 2); 33)
8*LFY	e2*93/81*0026*..	81	195/65R15		1); 2); 33)
8*LFY	e2*98/14*0026*..	81	195/65R15		1); 2); 33)
8*P8C	e2*93/81*0029*..	80	195/65R15		1); 2); 33)
8*RFN*	e2*98/14*0223*..	100	195/65R15 91H		*) ; not Coupe; 1); 2); 33)
8*RFR	e2*93/81*0088*..	99	195/65R15		1); 2); 33)
8*RFR	e2*98/14*0088*..	99	195/65R15		1); 2); 33)
8*RFV	e2*93/81*0025*..	97	195/65R15		1); 2); 33)
8*RFV	e2*98/14*0025*..	97	195/65R15		1); 2); 33)
8*RGX	e2*93/81*0073*..	108	195/65R15		1); 2); 33)
8*RHS*	e2*98/14*0264*..	79	195/65R15 91H		1); 2); 33)
8*RHY	e2*93/81*0087*..	66	195/65R15		1); 2); 33)
8*RHY	e2*98/14*0087*..	66	195/65R15 91H		1); 2); 33)
8*RHZ	e2*93/81*0188*..	80	195/65R15		1); 2); 33)
8*RHZ	e2*98/14*0188*..	80	195/65R15 91H		1); 2); 33)
8*RLZ*	e2*98/14*0222*..	103	195/65R15 91H		1); 2); 33)
8*6FZ*	e2*98/14*0092*..	85	195/65R15		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 17.05.2022



Auto Service

Seite: 3 von 3

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.