

Prüfbericht 22-00175-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000831

ANLAGE: 9.9
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 29.09.2022



Auto Service

Seite: 1 von 1

Manufacturer : FORD

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 37,5
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1925	R1-1925	Without	63,35		523	1876	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 133 Nm

commercial type: **TOURNEO COURIER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JU2	e1*98/14*0194*..	55 - 74	185/60R15		*); TOURNEO COURIER; from e1*98/14*0194*26; 1); 2); 33)
			195/60R15		

commercial type: **TRANSIT COURIER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JN8	e13*2007/46*1349*..	55 - 74	185/60R15		*); TRANSIT COURIER; 1); 2); 33)
			195/60R15		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.