Prüfbericht 22-00174-CX-GBM-02 zur Erteilung der ECE (E1) 124R- 000832

ANLAGE: 9.1 Radtyp: 16604108-30
Hersteller: MW Aftermarket Srl Stand: 17.05.2022



Auto Service

Seite: 1 von 1

Manufacturer : PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 27

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering	Centering	Permis	Permiss	Valid
			hole				from
					wheel	rolling	
	Wheel identification	Centering	(mm)		Load	Circumf	Produ
		identification				erence	ction
					(kg)	(mm)	date
R1-1640	R1-1640	Without	65		500	1928	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie
Tightening torque for fixing parts : 90 Nm

commercial type: PEUGEOT 207

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
	TT		205/55R16 91V		*): Front wheel
VV), FIOHL WHEEL
		66 - 128	195/55R16 87V		drive;
			195/55R16 91V		1); 2); 33)

^{*)} The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale-names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.