

Prüfbericht 22-00174-CX-GBM-02
zur Erteilung der ECE (E1) 124R- 000832

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16604108-30

Stand: 17.05.2022



Auto Service

Seite: 1 von 2

Manufacturer : CITROEN**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2

Off set(mm) : 23

Hole circle (mm)/number of holes : 108/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1747	R1-1747	Without	65		528	1894	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : CITROENMounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : SH****; SH; S****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : S; SH

Tightening torque for fixing parts : 100 Nm

commercial type: **CITROEN C3, DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S****	e2*2007/46*0003*..	44 - 115	195/55R16		*) ; 3-door; 5-door; 1); 2); 33)

commercial type: **CITROEN C3, DS3, DS3 CABRIO,**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S	e2*2007/46*0003*..	44 - 88	195/55R16 87		744; 77E; 1); 2); 33)
		44 - 110	195/55R16 81		
		50 - 115	195/55R16 82V		

commercial type: **CITROEN C3 PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SH	e2*2007/46*0110*..	66 - 88	195/55R16 84		1); 2); 33)
SH****	e2*2001/116*0371*..	66 - 88	195/55R16 91		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.

77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.

Prüfbericht 22-00174-CX-GBM-02
zur Erteilung der ECE (E1) 124R- 000832

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16604108-30

Stand: 17.05.2022



Auto Service

Seite: 2 von 2

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.