

Prüfbericht 22-00361-CX-GBM-03
zur Erteilung der ECE (E1) 124R- 000849

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 26.10.2022



Auto Service

Seite: 1 von 1

Manufacturer : SUZUKI**Wheel dates:**

Wheel size according to standard : 6 J X 16 CH

Off set(mm) : 50

Hole circle (mm)/number of holes : 114,3/5

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1878 MWRO	R1-1878	Without	60		535	1990	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SUZUKI

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

commercial type: **SX4, SUZUKI SX4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JY	e4*2007/46*0779*..	88	205/60R16		*) SX4 S-Cross; to e4*2007/46*0779*03; 744; 1); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.