

**Prüfbericht 22-00361-CX-GBM-03**  
**zur Erteilung der ECE (E1) 124R- 000849**

**ANLAGE: 9.3**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64  
 Stand: 26.10.2022



Auto Service

Seite: 1 von 3

**Manufacturer** : FCA, FIAT, NISSAN, OPEL / VAUXHALL, RENAULT

**Wheel dates:**

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 50  
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1896 MWFR	R1-1896	Without	66		868	2092	47/14
R1-1896 MWRO	R1-1896	Without	66		868	2092	17/17

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : FCA

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **TALENTO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FJL	e2*2007/46*0496*..	70 - 107	215/65R16C		*) ; TALENTO from e2*2007/46*0497*01; 1); 2); 33)

**Manufacturer** : FCA, FIAT, NISSAN, OPEL / VAUXHALL, RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : FIAT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

commercial type: **TALENTO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FFL	e2*2007/46*0497*..	66 - 107	205/65R16C 215/65R16C		744; 1); 2); 33)

**Manufacturer** : FCA, FIAT, NISSAN, OPEL / VAUXHALL, RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : NISSAN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 142 Nm

**Prüfbericht 22-00361-CX-GBM-03**  
**zur Erteilung der ECE (E1) 124R- 000849**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 26.10.2022



Auto Service

Seite: 2 von 3

commercial type: **NISSAN PRIMASTAR, NV300**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
J4	e2*98/14*0271*..	66 - 70	205/65R16C		*); NV300 from e2*98/14*0271*35; 1); 2); 33)
			215/65R16C		
		85 - 107	205/65R16C		
			215/65R16C		

commercial type: **PRIMASTAR, NV300**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
4	e2*2007/46*0037*..	66 - 103	205/65R16C		1); 2); 33)
			215/65R16C		

**Manufacturer** : FCA, FIAT, NISSAN, OPEL / VAUXHALL, RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : OPEL / VAUXHALL

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **VIVARO-B**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F7	e1*2007/46*0575*..	66 - 107	205/65R16C		*); 1); 2); 33)
			215/65 R16C		
X83	e1*98/14*0170*..	66 - 103	205/65R16C		*); VIVARO-B from e1*98/14*0170*30; 1); 2); 33)
		66 - 107	215/65R16C		

**Manufacturer** : FCA, FIAT, NISSAN, OPEL / VAUXHALL, RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : RENAULT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **RENAULT TRAFIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JL	e2*98/14*0213*..	66 - 103	205/65R16C		*); Model 2015; TRAFIC from e2*98/14*0213*48; 744; 1); 2); 33)
		66 - 107	215/65R16C		
JL	e2*98/14*0213*..	66 - 107	215/65R16C		*); Model 2015; TRAFIC from e2*98/14*0213*48; 1); 2); 33)
JL	e2*98/14*0213*..	66	205/65R16C		*); Model 2015; TRAFIC from e2*98/14*0213*48; 1); 2); 33)
		84 - 88	205/65R16C		
		103	205/65R16C		
L	e2*2007/46*0014*..	66 - 107	205/65R16C		744; 1); 2); 33)
			215/65R16C		

**Prüfbericht 22-00361-CX-GBM-03  
zur Erteilung der ECE (E1) 124R- 000849**

**ANLAGE: 9.3**

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 26.10.2022



Auto Service

Seite: 3 von 3

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 1) To be kept:
    - the standard wheel size and offset.
    - tyre size with service description (load and speed index) and tyre brand commitments
    - as well as limitations to snow tyres (M+S) from the car documents.
    - requirements and limitations of snow chains from the operating licence and the operation manual.
  - 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
  - 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.