

Prüfbericht 22-00361-CX-GBM-03
zur Erteilung der ECE (E1) 124R- 000849

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 26.10.2022



Auto Service

Seite: 1 von 2

Manufacturer : MERCEDES-BENZ, NISSAN EUROPE (F), RENAULT

Wheel dates:

Wheel size according to standard : 6 J X 16 H2

Off set(mm) : 38

Hole circle (mm)/number of holes : 114,3/5

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2112 MWRO	R1-2112	Without	66		650	1989	30/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : MERCEDES-BENZ

Mounting parts : conical collar bolt M12x1,5

commercial type: **Citan**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
MFK	e2*2018/858*00014*..	55 - 96	205/60R16		744; 1); 2); 33)

commercial type: **Citan, eCitan**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
MFK	e2*2018/858*00015*..	55 - 96	205/60R16		744; 77E; 1); 2); 33)

Manufacturer : MERCEDES-BENZ, NISSAN EUROPE (F), RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : NISSAN EUROPE (F)

Mounting parts : conical collar bolt M12x1,5

commercial type: **TOWNSTAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NFK	e2*2018/858*00024*..	96	205/60R16		744; 1); 2); 33)
NFK	e2*2018/858*00025*..	51 - 96	205/60R16		744; 1); 2); 33)

Manufacturer : MERCEDES-BENZ, NISSAN EUROPE (F), RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5

Prüfbericht 22-00361-CX-GBM-03
zur Erteilung der ECE (E1) 124R- 000849

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 26.10.2022



Auto Service

Seite: 2 von 2

commercial type: **KANGOO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
RFK	e2*2018/858*00001*..	55 - 96	205/60R16		744; 1); 2); 33)
RFK	e2*2018/858*00002*..	51 - 96	205/60R16		744; 1); 2); 33)

Restrictions

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.