

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.5
 Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28
 Stand: 06.05.2022



Auto Service

Seite: 1 von 1

Manufacturer : FORD

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 47,5
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2009	R1-2009	Without	63,35		441	1891	19/18

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 135 Nm

commercial type: **FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JHH	e9*2007/46*3142*..	52 - 103	195/55R16		75l; 1); 2); 33)

Restrictions

- 75l) The permitted axle load of the vehicle shall not exceed the double as on page 1 of this attachment mentioned wheel load under consideration of the mentioned rolling circumference, if necessary the increased axle load in trailer operation has to be adapted or to be cancelled
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.