

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.9
 Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28
 Stand: 06.05.2022



Auto Service

Seite: 1 von 2

Manufacturer : PSA Automobiles SA

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 32
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2059	R1-2059	Without	65		535	2092	07/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PSA Automobiles SA

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

commercial type: **Citroen C4, Citroen e-C4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
B	e9*2007/46*6816*..	81 - 114	215/65R16		744; 77E; 1); 2); 33)
B	e9*2007/46*6816*..	57	215/65R16		744; 77E; 1); 2); 33)
B	e9*2007/46*6816*..	74	215/65R16		744; 77E; 1); 2); 33)

commercial type: **DS3 CROSSBACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
U	e2*2007/46*0639*..	74 - 114	215/60R16 215/65R16		744; 77E; 1); 2); 33)

commercial type: **MOKKA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
U	e2*2007/46*0639*..	57 - 96	215/65R16		744; 1); 2); 33)

commercial type: **OPEL CORSA-F ab MJ 2019**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
U	e2*2007/46*0639*..	55 - 96	195/55R16		744; 77E; 1); 2); 33)

commercial type: **PEUGEOT 208, 2008**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
U	e2*2007/46*0639*..	57 - 114	215/60R16 215/65R16		744; 77E; 1); 2); 33)
U	e2*2007/46*0639*..	55 - 96	195/55R16		744; 77E; 1); 2); 33)

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.9
Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28
Stand: 06.05.2022



Auto Service

Seite: 2 von 2

Restrictions

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.