

Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840

ANLAGE: 9.10
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45
 Stand: 02.08.2023



Auto Service

Seite: 1 von 3

Manufacturer : **CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA, TOYOTA**

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 47
 Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2094	R1-2094	Without	65		700	2092	17/21

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts :

commercial type: **CITROEN C4 PICASSO, C4 SPACETOURER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
3	e2*2007/46*0356*..	96 - 133	205/60R16		744; 1); 2); 33)

Manufacturer : **CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA, TOYOTA**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **OPEL AUTOMOBILE GmbH**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 115 Nm

commercial type: **COMBO, COMBO-e CARGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0623*..	55 - 96	205/60R16 215/65R16		*) ; COMBO; 77E; 1); 2); 33)
E	e2*2007/46*0623*..	55 - 96	205/60R16 215/65R16		744; 77E; 1); 2); 33)
E	e2*2007/46*0623*..	57	215/65R16		744; 77E; 1); 2); 33)

commercial type: **COMBO LIFE, COMBO-e LIFE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0622*..	57	205/60R16		744; 77E; 1); 2); 33)
E	e2*2007/46*0622*..	56 - 96	205/60R16		77E; 1); 2); 33)
E	e2*2007/46*0622*..	56 - 96	205/60R16		744; 77E; 1); 2); 33)

Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840

ANLAGE: 9.10
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45
 Stand: 02.08.2023



Auto Service

Seite: 2 von 3

Manufacturer : **CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA, TOYOTA**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **PSA Automobiles SA**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **PARTNER, BERLINGO, RIFTER, DOBLO, e-RIFTER, e-PARTNER, e-BERLINGO, e-DOBLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0625*..	55 - 96	205/60R16 215/65R16		744; 77E; 1); 2); 33)
E	e2*2007/46*0625*..	55 - 96	205/60R16 215/65R16); RIFTER; BERLINGO; PARTNER; 77E; 1); 2); 33)

commercial type: **PARTNER, RIFTER, BERLINGO, DOBLO, e-RIFTER, e-BERLINGO, e-DOBLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0624*..	56 - 96	205/60R16 215/65R16); RIFTER; BERLINGO; 1); 2); 33)
E	e2*2007/46*0624*..	56 - 96	205/60R16 215/65R16		744; 1); 2); 33)
E	e2*2007/46*0624*..	57	205/60R16 215/65R16		744; 1); 2); 33)

Manufacturer : **CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA, TOYOTA**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **TOYOTA**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 115 Nm

commercial type: **PROACE CITY, PROACE CITY ELECTRIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0686*..	57	205/60R16 215/65R16		744; 1); 2); 33)
E	e2*2007/46*0686*..	56 - 96	215/65R16		1); 2); 33)
E	e2*2007/46*0686*..	56 - 96	205/60R16 215/65R16		744; 1); 2); 33)

commercial type: **PROACE CITY VERSO, PROACE CITY VERSO ELECTRIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0685*..	100	205/60R16		744; 77E; 1); 2); 33)
E	e2*2007/46*0685*..	75 - 96	205/60R16		77E; 1); 2); 33)
E	e2*2007/46*0685*..	75 - 96	205/60R16		744; 77E; 1); 2); 33)

**Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.10**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 3 von 3

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.