

Prüfbericht 20-00295-CX-GBM-06**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.12**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 1 von 3

Manufacturer : CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA, TOYOTA

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 47
Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1887.MWRO	R1-1887	Without	65		650	2092	20/23

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **CITROEN C4 PICASSO, C4 SPACETOURER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
3	e2*2007/46*0356*..	96 - 133	205/60R16		*) ; not electric; 744; 1); 2); 33)
3	e2*2007/46*0356*..	68 - 121	205/60R16	12K; 51G	*) ; C4 Picasso; C4 Grand Picasso; not electric; 1); 2); 3)
3	e2*2007/46*0356*..	68 - 121	205/60R16		*) ; not electric; 744; 1); 2); 33)

Manufacturer : CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA, TOYOTA

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : OPEL AUTOMOBILE GmbH

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

commercial type: **COMBO, COMBO-e CARGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0623*..	55 - 96	205/60R16		*) ; not electric; 744; 75I; 77E; 1); 2); 33)
			215/65R16		
E	e2*2007/46*0623*..	56 - 96	205/60R16		*) ; not electric; 744; 75I; 77E; 1); 2); 3); 11); 33)

Prüfbericht 20-00295-CX-GBM-06**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.12**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 2 von 3

commercial type: **COMBO LIFE, COMBO-e LIFE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0622*..	56 - 96	205/60R16		*) ; not electric; 744; 75l; 77E; 1); 2); 3); 11); 33)
E	e2*2007/46*0622*..	56 - 96	205/60R16		*) ; not electric; 744; 77E; 1); 2); 33)

Manufacturer : CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA,
TOYOTA

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PSA Automobiles SA

Mounting parts :

commercial type: **PARTNER, BERLINGO, RIFTER, DOBLO, e-RIFTER, e-PARTNER, e-BERLINGO, e-DOBLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0625*..	55 - 96	205/60R16		*) ; not electric; 744; 75l; 77E; 1); 2); 11); 33)
			215/65R16		

commercial type: **PARTNER, RIFTER, BERLINGO, DOBLO, e-RIFTER, e-BERLINGO, e-DOBLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0624*..	56 - 96	205/60R16		*) ; not electric; 744; 1); 2); 33)
			215/65R16		
E	e2*2007/46*0624*..	56 - 96	205/60R16		*) ; not electric; 744; 75l; 1); 2); 3); 11); 33)
			215/65R16		

Manufacturer : CITROEN, OPEL AUTOMOBILE GmbH, PSA Automobiles SA,
TOYOTA

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : TOYOTA

Mounting parts :

commercial type: **PROACE CITY VERSO, PROACE CITY VERSO ELECTRIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0685*..	75 - 96	205/60R16		*) ; not electric; 744; 77E; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Prüfbericht 20-00295-CX-GBM-06**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.12**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 3 von 3

Restrictions

- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 75I) The permitted axle load of the vehicle shall not exceed the double as on page 1 of this attachment mentioned wheel load under consideration of the mentioned rolling circumference, if necessary the increased axle load in trailer operation has to be adapted or to be cancelled
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 3) Only for vehicles from date of manufacture 04.2000.
- 11) The permissible axle load of the vehicle shall not be bigger than the twice of the chapter I. Overview listed wheel load under consideration of the mentioned rolling circumference. Where applicable the increased axle load has to be adapted or cancelled in trailer operation.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.