

**Prüfbericht 20-00295-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840**

**ANLAGE: 9.5**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45  
 Stand: 02.08.2023



Auto Service

Seite: 1 von 2

**Manufacturer : FORD**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50  
 Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1886	R1-1886	Without	63,35		678	1989	51/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : FORD**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad,  
 for Type : PU2; DM2

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad, for Type : PJ2

Tightening torque for fixing parts : 120 Nm for Type : PJ2; PU2  
 120 Nm ( Nur C-MAX ) for Type : DM2  
 130 Nm for Type : DM2

commercial type: **FORD C-MAX / KUGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	100 -120	235/60R16 100		*); til modelyear 2012; until e13*2001/116*0109*31; All-wheel drive; Front wheel drive; 1); 2); 33)
		147	235/60R16 91V		
DM2	e13*2001/116*0109*..	85 - 134	215/65R16		*); Only Kuga from Modelyear 2013; from e13*2001/116*0109*31; 1); 2); 33)
			235/60R16		
DM2	e13*2001/116*0109*..	66 - 107	205/55R16 91		*); C-MAX only; 1); 2); 33)
		81 - 107	205/55R16 M+S		

commercial type: **TOURNEO CONNECT,TRANSIT CONNECT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PJ2	e1*2001/116*0207*..	55 - 125	205/60R16		1); 2); 33)
			205/60R16 M+S		
			215/55R16		
			215/55R16 M+S		

**Prüfbericht 20-00295-CX-GBM-06****zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.5**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 2 von 2

commercial type: **TRANSIT CONNECT, TOURNEO CONNECT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PU2	e1*2007/46*0272*..	55 - 110	205/60R16		1); 2); 33)
			205/60R16 M+S		
			215/55R16		
			215/55R16 M+S		

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.