

**Prüfbericht 21-00319-CX-GBM-07**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

**ANLAGE: 9.16**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62  
 Stand: 21.04.2022



Auto Service

Seite: 1 von 1

**Manufacturer : Nissan International S. A., RENAULT**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 32  
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2076	R1-2076	Without	66		535	2092	38/21

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : Nissan International S. A.**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

commercial type: **Nissan Juke**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F16	e9*2007/46*6697*..	84 - 86	215/65R16		744; 1); 2); 33)

**Manufacturer : Nissan International S. A., RENAULT**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

commercial type: **CAPTUR, CAPTUR E-TECH PLUG-IN HYBRID**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
RJB	e2*2007/46*0684*..	70 - 113	215/65R16		744; 1); 2); 33)

**Restrictions**

744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.