

Prüfbericht 21-00319-CX-GBM-07**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847****ANLAGE: 9.3**

Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62

Stand: 21.04.2022



Auto Service

Seite: 1 von 1

Manufacturer : Nissan International S. A.**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 40
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1740	R1-1740	Without	66		608	2092	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : Nissan International S. A.

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 113 Nm

commercial type: **NISSAN QASHQAI,QASHQAI + 2**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
J10	e11*2001/116*0295*..	76 - 110	215/65R16 98		*) ; Nissan Qashqai short; Nissan Qashqai +2 (long); 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.