

Prüfbericht 21-00319-CX-GBM-07**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847****ANLAGE: 9.7**

Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62

Stand: 21.04.2022



Auto Service

Seite: 1 von 1

Manufacturer : TOYOTA**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16

Off set(mm) : 45

Hole circle (mm)/number of holes : 114,3/5

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1862	R1-1862	Without	60		575	1928	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : TOYOTA

Mounting parts : conical collar nut M12x1,5

Tightening torque for fixing parts : 103 Nm for Type : E15J(a); HE15U(a)
110 Nm for Type : E15UT(a)commercial type: **AURIS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E15J(a)	e11*2001/116*0299*..	66 - 108	205/55R16 91V		1); 2); 33)
E15UT(a)	e11*2001/116*0305*..	66 - 97	205/55R16 91V		*) ; AURIS TOURING SPORTS; from e11*2001/116*0305*15; 1); 2); 33)
E15UT(a)	e11*2001/116*0305*..	66 - 130	205/55R16 91V		1); 2); 33)
E15UT(a)	e11*2001/116*0305*..	66 - 97	205/55R16		*) ; from e11*2001/116*0305*14; Station wagon; Hatchback; Front wheel drive; 1); 2); 33)
HE15U(a)	e11*2007/46*0018*..	73	205/55R16 91V		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.