

Prüfbericht 21-00319-CX-GBM-07
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847

ANLAGE: 9.8
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62
 Stand: 21.04.2022



Auto Service

Seite: 1 von 2

Manufacturer : Nissan International S. A., RENAULT

Wheel dates:

Wheel size according to standard : 6 1/2 JJ X 16 CH Off set(mm) : 40
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1897	R1-1897	Without	66		635	2092	47/14
R1-1897.MWRO	R1-1897	Without	66		635	2092	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : Nissan International S. A.

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad, for Type : ZE0; C13; F15

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : J11; (Produktion UNITED KINGDOM)

Tightening torque for fixing parts : 108 Nm for Type : ZE0
 113 Nm for Type : C13; J11
 118 Nm for Type : F15

commercial type: **NISSAN JUKE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F15	e11*2007/46*0132*..	69 - 160	205/60R16		*) ; from e11*2007/46*0132*14; All-wheel drive; Front wheel drive; 1); 2); 33)
F15	e11*2007/46*0132*..	69 - 147 81	205/60R16 215/60R16		*) ; up to e11*2007/46*0132*13; All-wheel drive; Front wheel drive; 1); 2); 33)

commercial type: **NISSAN LEAF, NISSAN LEAF 24 kWh, NISSAN LEAF 30 kWh**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
ZE0	e11*2007/46*0230*..	80	205/55R16		*) ; E-car 80kW; 1); 2); 33)

commercial type: **NISSAN QASHQAI**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
J11	e11*2007/46*0963*..	81 - 120	215/65R16		*) ; All-wheel drive; Front wheel drive; 1); 2); 33)

Prüfbericht 21-00319-CX-GBM-07
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847

ANLAGE: 9.8
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62
 Stand: 21.04.2022



Auto Service

Seite: 2 von 2

commercial type: **PULSAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C13	e9*2007/46*3086*..	81 - 140	195/60R16 205/55R16		*) ; Front wheel drive; 1); 2); 33)

Manufacturer : Nissan International S. A., RENAULT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 113 Nm

commercial type: **KADJAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
RFE	e2*2007/46*0475*..	81 - 120	215/65R16		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.