

**Prüfbericht 21-00319-CX-GBM-07**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

ANLAGE: 9.9

Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62

Stand: 21.04.2022



Auto Service

Seite: 1 von 1

**Manufacturer** : KIA**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 47

Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1927	R1-1927	Without	67		525	2025	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : KIA

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 108 Nm

commercial type: **Soul**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PS	e4*2007/46*0825*..	91 - 113	205/60R16		1); 2); 33)
PSEV	e9*2007/46*6160*..	25 - 81	205/60R16		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.